

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER)

BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION 11805 SW 26 Street, Room 208 Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599 www.miamidade.gov/economy

NOTICE OF ACCEPTANCE (NOA)

Vision Hollow Metal Limited 400 Zenway Blvd., Unit 1 Woodbridge, Ontario L4H 057

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series LS1875 Outswing Double Steel Doors-LMI

APPROVAL DOCUMENT: Drawing No "AD10-11", titled "Series LS1875 Double/Single Outswing Steel Door", sheets 1 through 7 of 7, prepared by MCY Engineering, Inc., dated JUL 01, 2015, signed and sealed by Yiping Wang, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

Limitations:

- 1. See anchor options at jamb & threshold on sheet 2. Item #19 at exterior required for Water infiltration rating.
- 2. Double door with MG950 mullion will require Steel channel reinforcements for size exceeding 7' (84") High.
- 3. Electrical/Electronic function is not part of this approval, such functions to be reviewed and approved by AHJ

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, Woodbridge, Ontario, Canada, series/model and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises & renews NOA #12-0223.30 and consists of this page 1 and evidence pages E-1, as well as approval document mentioned above.

The submitted documentation was reviewed by Ishaq I. Chanda, P.E.



NOA No. 14-0513.04 Expiration Date: October 13, 2020 Approval Date: July 02, 2015

Page 1

Vision Hollow Metal Limited

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

- 1. Manufacturer's die drawings and sections (Submitted under file # see below).
- 2. Drawing No "AD10-11", titled "Series LS1875 Double/Single Outswing Steel Door", sheets 1 through 7 of 7, prepared by MCY Engineering, Inc., dated JUL01, 2015, signed and sealed by Yiping Wang, P.E.
- B. TESTS (Submitted under files #12-0223.30 /#10-0420.02)
 - 1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94 (w/Exterior astragal)
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

Along with manufacturer's parts and section drawings of double outswing steel doors, marked by Fenestration Testing Lab, Test Report No. **FTL-6222**, dated 05/18/10, signed and sealed by Jorge Causo, P. E.

This test report was revised by an addendum letter issued by Fenestration testing lab, dated June 17, 2010, signed and sealed by Jorge Causo, P. E.

C. CALCULATIONS

1. Anchor verification calculations and structural analysis, complying with FBC2014 (5th Edition), prepared by MCY Engineering, Inc., dated APR 21, 2015, signed and sealed by Yiping Wang, P. E.

D. OUALITY ASSURANCE

1. Miami Dade Department of Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS (Submitted under files #12-0223.29/#10-0623.02)

1. Tensile test report # FTL-6222, dated 05/18/10 prepared by fenestration Testing lab, signed & sealed by Jorge Causo, P.E.

F. STATEMENTS

- 1. Letter of conformance to FBC 2014 (5th edition) and No Financial interest dated May 01, 2015, prepared by MCY Engineering, Inc., signed and sealed by Yiping Wang, P.E.
- 2. Letter of conformance to FBC 2007 & "No financial interest" dated 05/30/10, signed and sealed by Yiping Wang, P.E.(submitted under file # 10-0623.02).
- 3. Lab compliance as part of the above referenced test report.


G. OTHER


- 1. This revises & renews NOA #12-0223.30, expiring on 10/13/20.
- 2. Distributor Agreement between Vision Hollow Metal Ltd., Ontario Canada and Precision Building Products, Florida USA, dated 04/13/15, signed by Nick Siragusa and Jacques Rousseau, respectively, on behalf of their companies.


4shaq I. Chanda, P.E. Product Control Examiner NOA No. 14-0513.04


Expiration Date: October 13, 2020

Approval Date: July 02, 2015











HINGES

STEEL MOTISE HINGES FOUR PER LEAF AT 10" FROM BOTTOM TO C.L. OF HINGE. 12" FROM TOP TO C.L. OF HINGE AND 26" O.C. MAX.

ALL HINGES FASTENED TO FRAME WITH (4) 12-24 x 1/2" FH MS AND TO PANEL WITH


(4) 12-24 x ½" FH MS





W/ LOCK OPTION #1 (RIM PANIC & MULLION)

LOCK OPTIONS



LOCK OPTIONS FOR DOUBLE DOORS ACTIVE LEAF CAN APPLY FOR SINGLE DOORS

ACTIVE LEAF

"DESIGN HARDWARE 2000 SERIES" PANIC EXIT DEVICE LOCATED AT PANELS AT 40" FROM BOTTOM, FASTENED WITH (6) 14 x 11/2" FH SDS.


INACTIVE LEAF

"DESIGN HARDWARE 2000 SERIES" PANIC EXIT DEVICE LOCATED AT PANELS AT 40" FROM BOTTOM, FASTENED WITH (6) 14 x 11/2" FH SDS.

LOCK OPTION #1 MULLION

DOOR W/ PANIC EXIT **DEVICE & MULLION**

'LOCKWOOD 950F MULLION " (2) SURFACE MOUNT METALLIC KEEPERS 40" FROM BOTTOM WITH (3) #10 x 1 1/4" FH SDS



LOCK OPTION #2

DOOR W/ CYLINDRICAL **LOCK & DEAD BOLT**

ACTIVE LEAF

"SCHLAGE AL53PD SERIES" LOCATED AT 391/2" FROM BOTTOM, FASTENED WITH (2) 8 x 3/4" MTS.

"SINGLE CYLINDER DEADBOLT LOCK" LOCATED AT 471/4" FROM BOTTOM WITH (2) 1/4-28 x 11/6" PH MS AND (2) 8 x 3/4" FH SMS.


INACTIVE LEAF

"YVES FB458 MORTISE FLUSHBOLTS"
LOCATED AT TOP AND BOTTOM, FASTENED WITH (4) 8 x 3/4" FH MULTI THREAD SCREWS.

STRIKE PLATE 39-1/2" FROM BOTTOM WITH (2) #12 X1" FH MULTI THREAD SCREWS

STRIKE PLATE AT MIDDLE SPAN OF FRAME HEAD WITH (2) #8 X3/4" FH MULTI THREAD SCREWS

STRIKE PLATE AT MIDDLE SPAN OF THREHOLD WITH (2) #8 X1 1/2" FH MULTI THREAD SCREWS



ACTIVE LEAF

"SCHLAGE L9453P MORTISE LOCK W/ INTEGRATED DEADBOLT" HANDLE LOCATED AT 37 %6" FROM BOTTOM, FASTENED WITH (2) 10 x 3/4" MTS. DEADBOLT LOCATED 40 5/8" FROM BOTTOM FASTENED WITH (2) 12x1" FH MULTI THREAD SCREWS

INACTIVE LEAF

"IVES FB458 MORTISE FLUSHBOLTS" LOCATED AT TOP AND BOTTOM, FASTENED WITH (4)

LOCK OPTION #3 8 x 3/4" FH MTS.

DOOR W/ MORTISE LOCK & DEAD BOLT

STRIKE PLATE 39-1/2" FROM BOTTOM WITH (2) #12 X1" FH MULTI THREAD SCREWS

FLUSH MOUNT METALLIC FLUSH BOLT AND FLUSH GUIDE TOP AND BOTTOM WITH (2) #8 X3/4" FH MULTI THREAD **SCREWS**

MIAMI DADE COUNTY

PRODUCT REVISED ne complying with the Florida Duidieu Code Acceptance No 14-05/3.0 Expiration Date 10/13/2

YIPING WANG, P.E. FLORIDA REGISTRATION PE #55983 C.A.N. 28677

JUL 01 2015

SERIES LS1875 DOUBLE/SINGLE OUTSWING STEEL DOOR (LMI) VISION HOLLOW METAL LIMITED 400 ZENWAY BLVD., UNIT #1 WOODBRIDGE, ON L4HOS7 91: (877) 984 - 8465 Fax: (905) 851 - 126

305.271.(786.573.

a, E,

STE.205A

8501 SW 124AVE. STE.205A MIAMI, FL. 33183 www.MCYEngineering.com

MCY ENGINEERING, GLAZING CONSULTANT

S 5

DATE SCALE DRAWN E.D -T.G.

AD10-11

4 OF 7

| | | | | BILL OF MATERIALS | |
|----------|----------|-------------|------------|---|---|
| ITEM NO. | PART NO. | MATERIAL | QUANTITY | DESCRIPTION | MANF./SUPPLIER/REMARKS |
| 1) | - | STEEL | AS REQ'D. | FRAME HEAD/JAMB (2" x 5 ¾") | 18 GA.(0.053"MIN.) GALVANNEAL STEEL (Fy = 54 KSI MIN.) |
| 2 | - | STEEL | AS REQ'D. | DOOR FACE SHEETS (48" x 96" x 0.044") | 18 GA.(0.044" MIN.) GALVANNEAL STEEL (Fy = 54 KSI MIN.) |
| 3 | 520S | ALUMINUM | 1 | BUMPER TRESHOLD (5" x ½" x 0.094") | HAGER |
| 4 | S88_ | VINYL | AS REQD. | ADHESIVE VINYL BULB | PEMKO |
| 5 | - | STEEL | 4 PER LEAF | HINGES | HAGER / DESIGN HARDWARE |
| 6 | H | STEEL | | MASONRY WIRE ANCHOR | 0.173 DIA. Fy = 60 PSI |
| 7 | - | STEEL | AS REQ'D. | CLOSER BOX (1 \%6" x 4\%6" x 0.053") | 16 GA. GALVANNEAL STEEL |
| 8 | - | STEEL | AS REQ'D. | END CHANNEL (1 ½" x 1 ½" x 0.053") | 16 GA. GALVANNEAL STEEL |
| 9 | | STEEL | AS REQ'D. | HINGE REINFORCEMENT | 10 GA. GALVANNEAL STEEL |
| 10 | - | STEEL | AS REQ'D. | EMA 18GA ANCHOR (PIPE) | VISION HOLLOW METAL |
| (1) | _ | STEEL | AS REQ'D. | EMA 18GA ANCHOR OPTION (BUTTERFLY) | VISION HOLLOW METAL |
| (12) | - | STEEL | 1 | CYLINDRAL LOCK REINFORCING | - |
| (13) | - | | AS REQ'D. | HONEY COMB 1" CELL | - |
| (14) | - | VINYL/STEEL | AS REQ'D. | TOP CAP OPTIONAL | VISION HOLLOW METAL |
| (15) | MG 950F | STEEL | AS REQ'D. | 2x3x1/8" REMOVABLE MULLION | LOCKWOOD Fy min. = 46 KSI |
| 16) | A0010 | STEEL | AS REQ'D. | ASA STRIKE REINFORCEMENT | VISION HOLLOW METAL |
| 17 | A0024 | STEEL | 1 | MORTISE BOX REINFORCMENT | VISION HOLLOW METAL |
| (18) | A0051 | STEEL | 2 / PANEL | RIM PANIC BOX 14" LG. | VISION HOLLOW METAL |
| (19) | - | STEEL | AS REQ'D | 1 3/4" x 0.12" THK ASTRAGAL | VISION HOLLOW METAL |
| 20 | - | STEEL | AS REQ'D | FLUSHBOLT GUIDE | VISION HOLLOW METAL FRODUCT HAVISED |
| (21) | - | STEEL | AS REQ'D | REVERSABLE FLUSHBOLT HEAD REINFORCEMENT | VISION HOLLOW METAL Building Code |
| 22 | 2000 | STEEL | AS REQ'D | SERIES 2000 DESIGN HARDWARE PANIC EXIT DEVICE | DESIGN HARDWARE Acceptance No 19-0 5/3-09 Expiration Date 70//3/20 |
| 23 | AL53PD | STEEL | AS REQ'D | SCHLAGE A1-53 PD CYLINDRICAL LOCK & DEAD BOLT | SCHLAGE By Shami Dade Freduct Control |
| 24) | - | STEEL | AS REQ'D | SCHLAGE L9453 MORTISE LOCK W/ INTEGRATED DEADBOLT | SCHLAGE |
| 25) | - | STEEL | AS REQ'D | IVES FB458 MANUAL FLASH BOLTS | IVES |
| | | • | | | YIPING WANG, R.E. |

MIAMI DADE COUNTY

Product Control

YIPING WANG P.E.

PLORIDA REGISTRATION
PE #55983
C.A.N. 28677

DRAWN ED-T.G.
PROJECT

DRAWDING NO.
AD10—11

5 OF 7

8501 SW 124AVE. STE.205A P. 305.271.0117 MAMI, FL. 33183 F. 786.573.5063 www.MCYEngineering.com MCY.Engineering

SERIES LS1875 DOUBLE/SINGLE OUTSWING STEEL DOOR (LMI)

VISION HOLLOW METAL LIMITED

400 ZENWAY BLVD., UNIT #1

WOODBRIDGE, ON L4HOS7

Tel: (877) 984 - 8465 Fex: (905) 851 - 1261

MCY ENGINEERING, INC. GLAZING CONSULTANTS

